

[Code](#), [Display](#), [Hardware](#), [Nuetzliche Links](#)

Parallax Serial LCD



Nützliche Links

- <https://github.com/gatonero/parallaxLCD>
- [Diskussion auf python-forum.de](#)

Quellen

- [Arduino Parallax LCD Library](#)

Library

The ESP32 has three hardware UARTs: UART0, UART1 and UART2. They each have default GPIO assigned to them, however depending on your ESP32 variant and board, these pins may conflict with embedded flash, onboard PSRAM or peripherals.

Any GPIO can be used for hardware UARTs using the GPIO matrix, so to avoid conflicts simply provide tx and rx pins when constructing. The default pins listed below.

	UART0	UART1	UART2
tx	1	10	17

Last
update: digitaless:hardware:displays:parallax_serial_lcd https://gatonero.duckdns.org/!digitaless/digitaless:hardware:displays:parallax_serial_lcd
25.05.2025

	UART0	UART1	UART2
rx	3	9	16

- [MicroPython Dokumentation class UART – duplex serial communication bus](#)
- [MicroPython UART Quick Reference](#)

From:

<https://gatonero.duckdns.org/!digitaless/> - **Digitaless**

Permanent link:

https://gatonero.duckdns.org/!digitaless/digitaless:hardware:displays:parallax_serial_lcd

Last update: **25.05.2025**

